



Update Your Bearing Inventory

Factory Authorized - Relubrication to Your Specifications



ISO Class 6 (Class 1000) Cleanroom Facility Near Seattle, WA

- AS9100/ISO and Factory Certified Facility
- Complete Documentation and Traceability for All Orders
- Relubricate and Refresh Expired Bearing Inventory
- Extensive Range of Lubricant Options
- Small and Large Volume Orders Accepted (From 1 to 100,000)
- Same Day Service Available



National Precision Bearing
8152 304th Ave. S.E.
PO Box 5012
Preston, WA 98050

Toll Free: (800) 426-8038
Tel: (425) 222-5900
Fax: (425) 222-5950
Toll Free Fax: (888) 448-1153

Email: sales@nationalprecision.com
www.nationalprecision.com



Global Solutions on a National Level

COMMONLY LUBRICATED BEARING TYPES

- Miniature Ball Bearing
- Needle Roller Bearings
- Angular Contact Bearings
- Deep Groove Ball Bearings
- Medical Instrument Bearings
- Thin Section Bearings
- Track Roller Bearings
- Linear Bearings
- Metal-to-Metal Spherical Bearings

COMMONLY RELUBRICATED AIRFRAME BEARINGS

- | | |
|---------|---------|
| MS27640 | KP() |
| MS27641 | KP()A |
| MS27642 | KP()B |
| MS27644 | DPP() |
| MS27646 | B500DD |
| MS27647 | DW() |
| MS27648 | KP()BS |
| MS27649 | AW()AK |
| MS21428 | MB500DD |



Global Solutions on a National Level

Tel: (800) 426-8038
 Fax: (425) 222-5950
 Toll Free Fax: (888) 448-1153
 Email: sales@nationalprecision.com

LUBRICANT AND FILL SPECIFICATIONS

NPB stocks a wide variety of specialty lubricants including food grade, low outgassing, and corrosive resistant greases. Below is a table of commonly specified lubricants.

BRAND NAME	BASIC TYPE	OPERATING TEMP. F	USES
Windsor L-245X (MIL-L-6085)	Synthetic Oil	-65 to +300	Light general purpose oil. Low torque.
Beacon 325	Synthetic Grease	-65 to +250	General purpose grease. Low torque.
Royco 27 (MIL-PRF-23827)	Synthetic Grease	-100 to +275	Corrosion resistant. Heavy loads and high speed.
Rheotemp 500	Synthetic (Non-silicone) Grease	-65 to +350	Oxidation inhibitor. High temperature and high speed.
Mobil 28 (MIL-PRF-81322)	Synthetic Hydrocarbon Grease	-65 to +350	Low torque. Low speed oscillation.
SRI-2	Mineral Grease	-20 to +350	Long life. Water resistant. High speed and high temperature.
Krytox 240AC	Fluorinated Grease	-30 to +550	High temperature.
Multitemp SRL	Synthetic Grease	-40 to +300	Very quiet. Low torque.
Braycote Micronic 601EF	Perfluorinated Polyether Grease	-112 to +400	Low pressure/vacuum environments. Hostile chemical environments.
Aeroshell 33 (BMS3-33)	Synthetic Grease	-100+250	Corrosion resistant. Heavy loads.

Standard or special lubricant fill rates can be requested depending on type of bearing. Standard fill for miniature ball bearings is 25-35% fill, standard fill for many airframe type bearings is 80-100%. Grease Plating, centrifuge, and other special application methods are available on request.